

Galvanized Steel Conduits for Electrical Wires and Cables

CNS 2606 C4060 (EQUIVALENT TO JIS C8305)

THREADED

DESIGNATOR	O.D. (mm)	TOLERANCE ON O.D. (mm)	THICKNESS (mm)	WEIGHT (kg/m)	EFFECTIVE LENGTH OF THREADED PART (mm)	
					MAX.	MIN.
G16	21.0	±0.3	2.3	1.06	19	16
G22	26.5	±0.3	2.3	1.37	22	19
G28	33.3	±0.3	2.5	1.90	25	22
G36	41.9	±0.3	2.5	2.43	28	25
G42	47.8	±0.3	2.5	2.79	28	25
G54	59.6	±0.3	2.8	3.92	32	28
G70	75.2	±0.3	2.8	5.00	36	32
G82	87.9	±0.3	2.8	5.88	40	36
G92	100.7	±0.4	3.5	8.39	42	36
G104	113.4	±0.4	3.5	9.48	45	39

NONE THREADED

DESIGNATOR	O.D. (mm)	TOLERANCE ON O.D. (mm)	THICKNESS (mm)	WEIGHT (kg/m)
E19	19.1	±0.15	1.2	0.530
E25	25.4	±0.15	1.2	0.716
E31	31.8	±0.15	1.4	1.05
E39	38.1	±0.15	1.4	1.27
E51	50.8	±0.15	1.4	1.71
E63	63.5	±0.15	1.6	2.44
E75	76.2	±0.15	1.8	3.30

* TOLERANCE ON WEIGHT: + (NOT SPECIFIED) / -7%